

KLT-IRSW-OS05A10 V1.0

**OmniVision OS05A10 带红外开关 MIPI串行接口 固定焦距 500万像素
M12 摄像头模组**




摄像头模组型号	KLT-IRSW-OS05A10 V1.0	
图像感光芯片	OS05A10	红外开关
焦距	1.95 mm	输入电压: 3.3V ~ 5.5V
光圈	2.2	红外线: 645nm +/- 15nm
像素	2688 x 1944	AR: 700nm ~ 1000 nm
可视角度	180°(D) 171.5°(H) 118°(V)	运行 (IR白天时间)
镜头类型	1/2.7 英寸	红线: 负
镜头尺寸	22.20 x 21.50 x 12.96 mm	黑线: 正
模组尺寸	50.00 x 30.00 mm	操作 (AR 夜间)
模组类型	固定焦距	红线: 正
接口	MIPI串行	黑线: 负

配对连接器型号: **WP7A-S024VA1**



主板上的对应连接器。分开售卖。



OS05A10 5-megapixel product brief



Versatile 5-Megapixel PureCel® Sensor with High Dynamic Range for a Wide Range of Commercial Security and Consumer Applications



available in a lead-free package

OmniVision's low-power OS05A10 is a 5-megapixel image sensor that brings crisp 1080p high definition, 2K, and 5-megapixel video to a wide range of commercial security and consumer applications, including 360-degree full-view cameras. Built on OmniVision's advanced PureCel® pixel architecture, the OS05A10 utilizes backside illumination (BSI) technology to deliver enhanced low-light sensitivity and wide field of view (FOV).

Available in the popular 1/2.7-inch optical format, the OS05A10 enables video applications in widely used 4:3 and 16:9 aspect ratios. The sensor can capture 1080p full high definition slow-motion video at 120 frames per second (fps) and 2688 x 1944 resolution at 60 fps.

Additionally, the OS05A10 features a 12-degree chief ray angle (CRA) and a dual-exposure staggered high dynamic range (HDR) mode to enable excellent scene reproduction in difficult high-contrast lighting conditions.

The OS05A10 is compatible with MIPI and LVDS interfaces and comes in a chip scale package (CSP) of 6.6 mm x 5.9 mm.

Find out more at www.ovt.com.



Applications

- Security Cameras
- High Resolution Consumer Cameras
- Action Cameras

Product Features

- 2 μm x 2 μm pixel
- optical size of 1/2.7"
- programmable controls for:
 - frame rate
 - mirror and flip
 - cropping
 - windowing
- supports output formats:
 - 10/12-bit RAW RGB
- supports images sizes:
 - 5MP (2688x1944)
 - 1080p (1920x1080)
 - 720p (1280x720)
- supports 2x2 binning
- standard serial SCCB interface
- 12/10-bit ADC
- up to 4-lane MIPI/LVDS serial output interface (supports maximum speed up to 1500 Mbps/lane)
- 2-exposure staggered HDR support
- programmable I/O drive capability
- light sensing mode (LSM)
- PLL with SCC support
- support for frame sync

OS05A10




Ordering Information

- OS05A10-H79A-Z
(color, lead-free, 79-pin CSP)

Product Specifications

- active array size: 2688 x 1944
- lens chief ray angle: 11° linear
- power supply:
 - core: 1.2V
 - analog: 2.8V
 - I/O: 1.8V
- power requirements:
 - active: 221 mW
 - standby: 210 μA
 - XSHUTDOWN: 0.6 μA
- temperature range:
 - operating: -30°C to +85°C junction temperature
 - stable image: 0°C to +60°C junction temperature
- output formats: 10/12-bit RGB RAW
- lens size: 1/2.7"
- input clock frequency: 6 - 27 MHz
- scan mode: progressive
- maximum image transfer rate:
 - 2688x1944: 60 fps
 - 2688x1520: 60 fps
- maximum exposure interval: VTS - 8
- minimum exposure interval: 2 t_{row}
- pixel size: 2.0 μm x 2.0 μm
- image area: 5434.56 μm x 3948.05 μm
- package dimensions:
 - CSP: 6638.8 μm x 5935 μm

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: + 1 408 567 3000
Fax: + 1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and OmniPixel are registered trademarks of OmniVision Technologies, Inc. OmniBSI-Z is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.



OmniVision