


**JAL-GC2235-L1F****GalaxyCore GC2235 MIPI Interfaz Foco fijo 2MP Módulo de cámara**

<b>Módulo de cámara No.</b>	<b>JAL-GC2235-L1F</b>
<b>Sensor de imagen</b>	GC2235
<b>EFL</b>	2.95 mm
<b>F.NO</b>	2.8
<b>Pixel</b>	1600 x 1200 (UXGA)
<b>Ángulo de visión</b>	60°
<b>Tipo de lente</b>	1/5 pulgada
<b>Dimensiones de la lente</b>	6.5 x 6.5 x 5 mm
<b>Tamaño del módulo</b>	13.6 x 8.4 mm
<b>Tipo de módulo</b>	Foco fijo
<b>Interfaz</b>	MIPI

**N. ° de pieza del conector de acoplamiento. AXE524124**

Conector de acoplamiento en la placa principal. Se vende por separado.



# GC2235 product brief



## *1/5" UXGA CMOS Image Sensor*

GC2235 is a high quality 2Mega CMOS image sensor, for mobile phone camera applications and digital camera products. GC2235 incorporates a 1616V x 1232H pixel array, on-chip 10-bit ADC, and image signal processor.

The full scale integration of high-performance and low-power functions makes the GC2235 best fit the design, reduce

implementation process, and extend the battery life of cell phones, PDAs, and a wide variety of mobile applications.

It provides RAW10 and RAW8 data formats with MIPI interface. It has a commonly used two-wire serial interface for host to control the operation of the whole sensor.

## Application

- Cellular Phone Cameras
- Notebook and desktop PC cameras
- PDAs
- Toys
- Digital still cameras and camcorders
- Video telephony and conferencing equipment
- Security systems
- Industrial and environmental systems
- 

## Product Features

- BSI process
- Output formats: Raw Bayer 10bit/8bit
- Support for image sizes: UXGA and 720P
- Interface support:
  - DVP parallel
  - MIPI(1\_lane/2\_lane)
- PLL support
- Windowing support
- Horizontal /Vertical mirror

## Product Specifications

- Optical Format: 1/5 inch
- Pixel Size: 1.75um x 1.75um(BSI)
- Active pixel array: 1616x1232
- ADC resolution: 10 bit ADC
- Max Frame rate: full resolution@30fps
- Power Supply:
  - AVDD28: 2.7~3.0V
  - DVDD18: 1.7~1.9V
  - IOVDD: 1.7~3.0V
- Power Consumption:
  - Active: 140mW
  - Standby: <100uA
- SNR: 37.4 dB
- Dark Current: 60 e-/sec@60°C
- Sensitivity: 6700 e-/lux-sec
- Dynamic Range: 61.7 dB
- Operating temperature: -20~70°C
- Stable Image temperature: 0~50°C
- Optimal lens chief ray angle (CRA): 25°(non-linear)
- Package type: CSP/wafer

## Functional block diagram

