

KLT-D6K-OV2643 V1.0

OmniVision OV2643 Parallèle DVP Interface Mise au point fixe 2MP M12
Module de caméra



Module de caméra No.	KLT-D6K-OV2643 V1.0
Capteur d'image	OV2643
EFL	2.6 mm
F.NO	2.2
Pixel	1600 x 1200 (UXGA)
Angle de vue	127°
Type d'objectif	1/4 pouce
Dimensions de l'objectif	14.0 x 14.0 x 13.91 mm
Taille du module	40.0 x 14.0 mm
Type de module	Mise au point fixe
Interface	Parallèle DVP
Modèle d'objectif IMT	IMT-4B12A005-6

Référence du connecteur d'accouplement. FH12-24S-0.5SH



Connecteur d'accouplement sur la carte principale. Vendu séparément.



OV2643 2MP product brief



High-Performance 2-Megapixel SOC Camera for the High-Volume, Feature Rich Phone Market



available in
a lead-free
package

Designed to address the increasing demand for 2-megapixel resolution cameras in mainstream feature phones, the OV2643 brings high-definition (HD) video and excellent low-light sensitivity to this high-volume market. The OV2643 targets high-performance applications in a 1/4-inch optical format that fits the critical 6.5 x 6.5 mm camera module size. The OV2643 implements OmniVision's advanced 2.2-micron OmniPixel3-HS™ architecture to achieve a sensitivity of 1250 mV/lux-sec, enabling excellent image quality under the most challenging lighting conditions.

The OV2643 is a system on a chip (SOC) CMOS image sensor with advanced image signal processing that allows it to offer the quality and functionality of most high-performance DSC cameras, including support for 720p HD video recording at 30 frames per second, excellent sensitivity and high quality image capture while meeting the cost, size and performance requirements of the feature phone market.

The OV2643 offers automatic image control functions, which include automatic exposure control, automatic white balance and automatic black level calibration. It also features all standard image quality controls such as color saturation, hue, gamma, sharpness (edge enhancement), lens correction, defective pixel canceling and noise canceling and support for black sun cancelation.

The OV2643 comes with a standard serial SCCB interface and digital video port (DVP) parallel output interface, offering support for UXGA, SVGA and 720p with programmable controls for frame rate as well as video operations.

Find out more at www.ovt.com.

Applications

- Mobile Phones
- Entertainment
- Notebooks and Webcams

Product Features

- ultra low power and low cost
- automatic image control functions:
 - automatic exposure control (AEC)
 - automatic white balance (AWB)
 - automatic band filter (ABF)
 - automatic black level calibration (ABLC)
- programmable controls for frame rate, AEC/AGC 16-zone size/position/weight control, mirror and flip, and windowing
- image quality controls: color saturation, hue, gamma, sharpness (edge enhancement), lens correction, defective pixel canceling, and noise canceling
- support for output formats: RAW RGB, RGB565/555, YUV422, YCbCr422 and GBR422
- support for images sizes: UXGA, SVGA, and 720p
- support for video operations
- support for horizontal and vertical sub-sampling, binning
- standard serial SCCB interface
- digital video port (DVP) parallel output interface
- on-chip phase lock loop (PLL)
- programmable I/O drive capability
- support for black sun cancellation
- built-in regulator for DVDD
- suitable for module size of 6.5 mm x 6.5 mm

OV2643



Ordering Information

- OV02643-A42A
(color, lead-free, 42-pin CSP3)

Product Specifications

- active array size: 1624 x 1212
- power supply:
 - core: 1.5 VDC $\pm 5\%$
 - analog: 2.6 - 3.0 V
 - I/O: 1.7 - 3.0 V
- power requirements:
 - active: 150 mW
 - standby: 30 μ A
- temperature range:
 - operating: -20°C to 70°C junction temperature
 - stable image: 0°C to 50°C junction temperature
- output formats: YUV422/YCbCr422, GBR422, RGB565/555, 8/10-bit RAW RGB data
- lens size: 1/4"
- lens chief ray angle: 25° non-linear
- input clock frequency: 6 - 27 and 54 MHz
- max S/N ratio: 39 dB
- dynamic range: 66 dB @ 8x gain
- maximum image transfer rate:
 - UXGA (1600x1200): 15 fps
 - SVGA (800x600): 30 fps
 - 720p (1280x720): 30 fps
- sensitivity: 1250 mV/lux-sec
- shutter: rolling shutter
- scan mode: progressive
- maximum exposure interval: 1227 x t_{row}
- gamma correction: programmable
- pixel size: 2.2 μ m x 2.2 μ m
- image area: 3590 μ m x 2710 μ m
- package dimensions: 5035 μ m x 4635 μ m

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: + 1 408 567 3000
Fax: + 1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and OmniPixel are registered trademarks of OmniVision Technologies, Inc. OmniPixel3-H5 is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.