



KLT-IRSW-OS05A10 V2.0

**OmniVision OS05A10 with IR Switch MIPI Interfaccia Messa a fuoco fissa 5MP M12
Modulo telecamera**




Modulo telecamera n.	KLT-IRSW-OS05A10 V2.0	
Sensore d'immagine	OS05A10	IR SWITCH
EFL	1.95 mm	Input Voltage: 3.3V ~ 5.5V
F.NO	2.2	IR: 645nm +/- 15nm
Pixel	2688 x 1944	AR: 700nm ~ 1000 nm
Vista ad angolo	180°(D) 171.5°(H) 118°(V)	Operation (IR Day Time)
Tipo di lente	1/2.7 pollice	Red Line: Negative
Dimensioni dell'obiettivo	22.20 x 21.50 x 12.96 mm	Black Line: Positive
Dimensione del modulo	50.00 x 30.00 mm	Operation (AR Night Time)
Tipo di modulo	Messa a fuoco fissa	Red Line: Positive
Interfaccia	MIPI	Black Line: Negative

Connettore di accoppiamento Codice. WP7A-S024VA1



Connettore di accoppiamento sulla scheda principale. Venduto separatamente.



OS05A10 5-megapixel product brief



Versatile 5-Megapixel PureCel® Sensor with High Dynamic Range for a Wide Range of Commercial Security and Consumer Applications



lead free
available in
a lead-free
package

OmniVision's low-power OS05A10 is a 5-megapixel image sensor that brings crisp 1080p high definition, 2K, and 5-megapixel video to a wide range of commercial security and consumer applications, including 360-degree full-view cameras. Built on OmniVision's advanced PureCel® pixel architecture, the OS05A10 utilizes backside illumination (BSI) technology to deliver enhanced low-light sensitivity and wide field of view (FOV).

Available in the popular 1/2.7-inch optical format, the OS05A10 enables video applications in widely used 4:3 and 16:9 aspect ratios. The sensor can capture 1080p full high definition slow-motion video at 120 frames per second (fps) and 2688 x 1944 resolution at 60 fps.

Additionally, the OS05A10 features a 12-degree chief ray angle (CRA) and a dual-exposure staggered high dynamic range (HDR) mode to enable excellent scene reproduction in difficult high-contrast lighting conditions.

The OS05A10 is compatible with MIPI and LVDS interfaces and comes in a chip scale package (CSP) of 6.6 mm x 5.9 mm.

Find out more at www.ovt.com.



Applications

- Security Cameras
- High Resolution Consumer Cameras
- Action Cameras

Product Features

- 2 μm x 2 μm pixel
- optical size of 1/2.7"
- programmable controls for:
 - frame rate
 - mirror and flip
 - cropping
 - windowing
- supports output formats:
 - 10/12-bit RAW RGB
- supports images sizes:
 - 5MP (2688x1944)
 - 1080p (1920x1080)
 - 720p (1280x720)
- supports 2x2 binning
- standard serial SCCB interface
- 12/10-bit ADC
- up to 4-lane MIPI/LVDS serial output interface (supports maximum speed up to 1500 Mbps/lane)
- 2-exposure staggered HDR support
- programmable I/O drive capability
- light sensing mode (LSM)
- PLL with SCC support
- support for frame sync

OS05A10




Ordering Information

- OS05A10-H79A-Z (color, lead-free, 79-pin CSP)

Product Specifications

- active array size: 2688 x 1944
- lens chief ray angle: 11° linear
- power supply:
 - core: 1.2V
 - analog: 2.8V
 - I/O: 1.8V
- power requirements:
 - active: 221 mW
 - standby: 210 μA
 - XSHUTDOWN: 0.6 μA
- temperature range:
 - operating: -30°C to +85°C junction temperature
 - stable image: 0°C to +60°C junction temperature
- output formats: 10/12-bit RGB RAW
- lens size: 1/2.7"
- input clock frequency: 6 - 27 MHz
- scan mode: progressive
- maximum image transfer rate:
 - 2688x1944: 60 fps
 - 2688x1520: 60 fps
- maximum exposure interval: VTS - 8
- minimum exposure interval: 2 t_{row}
- pixel size: 2.0 μm x 2.0 μm
- image area: 5434.56 μm x 3948.05 μm
- package dimensions:
 - CSP: 6638.8 μm x 5935 μm

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: + 1 408 567 3000
Fax: + 1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and OmniPixel are registered trademarks of OmniVision Technologies, Inc. OmniBSI-Z is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.



OmniVision