

**JAL-KA9-F299 V7.0****OmniVision OV2643 DVP Paralelo Interface Foco Fixo 2MP Módulo de Câmera**

<b>Módulo de câmara No.</b>	<b>JAL-KA9-F299 V7.0</b>
<b>Sensor de imagem</b>	OV2643
<b>EFL</b>	3.29 mm
<b>F.NO</b>	2.8
<b>Pixel</b>	1600 x 1200 (UXGA)
<b>Ângulo de visão</b>	68.7°
<b>Tipo de lente</b>	1/4 polegada
<b>Dimensões da lente</b>	8 x 8 x 4.85 mm
<b>Tamanho do Módulo</b>	50 x 12.5 mm
<b>Tipo de Módulo</b>	Foco Fixo
<b>Interface</b>	DVP Paralelo

**Acasalamento Parte conector No. FH12-24S-0.5SH**

Conector de acoplamento na placa principal. Vendido separadamente.



# OV2643 2MP product brief



## High-Performance 2-Megapixel SOC Camera for the High-Volume, Feature Rich Phone Market



available in a lead-free package

Designed to address the increasing demand for 2-megapixel resolution cameras in mainstream feature phones, the OV2643 brings high-definition (HD) video and excellent low-light sensitivity to this high-volume market. The OV2643 targets high-performance applications in a 1/4-inch optical format that fits the critical 6.5 x 6.5 mm camera module size. The OV2643 implements OmniVision's advanced 2.2-micron OmniPixel3-HS™ architecture to achieve a sensitivity of 1250 mV/lux-sec, enabling excellent image quality under the most challenging lighting conditions.

The OV2643 is a system on a chip (SOC) CMOS image sensor with advanced image signal processing that allows it to offer the quality and functionality of most high-performance DSC cameras, including support for 720p HD video recording at 30 frames per second, excellent sensitivity and high quality image capture while meeting the cost, size and performance requirements of the feature phone market.

The OV2643 offers automatic image control functions, which include automatic exposure control, automatic white balance and automatic black level calibration. It also features all standard image quality controls such as color saturation, hue, gamma, sharpness (edge enhancement), lens correction, defective pixel canceling and noise canceling and support for black sun cancelation.

The OV2643 comes with a standard serial SCCB interface and digital video port (DVP) parallel output interface, offering support for UXGA, SVGA and 720p with programmable controls for frame rate as well as video operations.

Find out more at [www.ovt.com](http://www.ovt.com).

## Applications

- Mobile Phones
- Entertainment
- Notebooks and Webcams

## Product Features

- ultra low power and low cost
- automatic image control functions:
  - automatic exposure control (AEC)
  - automatic white balance (AWB)
  - automatic band filter (ABF)
  - automatic black level calibration (ABLC)
- programmable controls for frame rate, AEC/AGC 16-zone size/position/weight control, mirror and flip, and windowing
- image quality controls: color saturation, hue, gamma, sharpness (edge enhancement), lens correction, defective pixel canceling, and noise canceling
- support for output formats: RAW RGB, RGB565/555, YUV422, YCbCr422 and GBR422
- support for images sizes: UXGA, SVGA, and 720p
- support for video operations
- support for horizontal and vertical sub-sampling, binning
- standard serial SCCB interface
- digital video port (DVP) parallel output interface
- on-chip phase lock loop (PLL)
- programmable I/O drive capability
- support for black sun cancellation
- built-in regulator for DVDD
- suitable for module size of 6.5 mm x 6.5 mm

# OV2643



## Ordering Information

- OV02643-A42A  
(color, lead-free, 42-pin CSP3)

## Product Specifications

- active array size: 1624 x 1212
- power supply:
  - core: 1.5 VDC  $\pm 5\%$
  - analog: 2.6 - 3.0 V
  - I/O: 1.7 - 3.0 V
- power requirements:
  - active: 150 mW
  - standby: 30  $\mu$ A
- temperature range:
  - operating: -20°C to 70°C junction temperature
  - stable image: 0°C to 50°C junction temperature
- output formats: YUV422/YCbCr422, GBR422, RGB565/555, 8/10-bit RAW RGB data
- lens size: 1/4"
- lens chief ray angle: 25° non-linear
- input clock frequency: 6 - 27 and 54 MHz
- max S/N ratio: 39 dB
- dynamic range: 66 dB @ 8x gain
- maximum image transfer rate:
  - UXGA (1600x1200): 15 fps
  - SVGA (800x600): 30 fps
  - 720p (1280x720): 30 fps
- sensitivity: 1250 mV/lux-sec
- shutter: rolling shutter
- scan mode: progressive
- maximum exposure interval: 1227 x  $t_{row}$
- gamma correction: programmable
- pixel size: 2.2  $\mu$ m x 2.2  $\mu$ m
- image area: 3590  $\mu$ m x 2710  $\mu$ m
- package dimensions: 5035  $\mu$ m x 4635  $\mu$ m

## Functional Block Diagram



4275 Burton Drive  
Santa Clara, CA 95054  
USA

Tel: + 1 408 567 3000  
Fax: + 1 408 567 3001  
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo and OmniPixel are registered trademarks of OmniVision Technologies, Inc. OmniPixel3-H5 is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.

OmniVision